

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 1 of 7  
Version: 1.1  
Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

### 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

**Product Brand Name:** XtraBond XB25 Acrylic Latex Sealant  
**Product Use:** Sealant & Adhesive  
**Proper DOT Shipping:** Caulking & Glaziers, NOI  
**DOT Hazard Classification:** NONE  
**Molecular Formula:** Mixture

**NFPA Profile:** Health 1      Flammability 0      Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

#### Company Contact Information

Premier Industrial Supply, Inc.  
4282B Strausser St. NW  
North Canton, OH 44720

#### Emergency Telephone Number

CHEMTREC: 800-424-9300 (24 hours)  
Telephone: 866-512-4583

### 2. HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

##### Acute Effects

Eye: Direct contact may cause moderate irritation.  
Skin: May cause slight irritation.  
Inhalation: Irritates respiratory passages very slightly.  
Oral: Low ingestion hazard in normal use.

##### Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.  
Inhalation: Irritation of the upper respiratory system.  
Oral: Repeated ingestion or swallowing large amounts may cause internal injury.

##### Signs and Symptoms of Overexposure

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

##### Medical Conditions Aggravated by Exposure

None generally recognized.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 2 of 7

Version: 1.1

Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
471-34-1	60	Calcium Carbonate	
		ACGIH TLV	10 mg/m3 as Dust
		OSHA PEL	15 mg/m3 Total Dust
		OSHA PEL	5 mg/m3 Respirable Fraction

### 4. FIRST AID MEASURES

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 – 20 minutes while holding the eyelid(s) open. If contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin:	Remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Wash affected area with soap and water.
Inhalation:	Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor is generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.
Oral:	Do not induce vomiting. Get medical attention immediately.

Note to Physician: Treat according to person's condition and specifics of exposure.

### 5. FIRE FIGHTING MEASURES

Flash Point:	Not applicable
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	Carbon dioxide, dry chemical or foam. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Water spray may be ineffective. If water is used, fog nozzles are preferable.
Unusual Fire Hazards:	None.

### 6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up:	Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may
-----------------------	---

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 3 of 7

Version: 1.1

Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills.

### 7. HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

### 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

#### Engineering Controls

Local Ventilation: Recommended.

General Ventilation: Recommended.

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

#### Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator: Respiratory protection is not needed under ambient conditions. If vapor is generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 4 of 7

Version: 1.1

Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

This material may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film.

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### Personal Protective Equipment for Spills

Eyes: Use full face respirator.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

## 9. PHYSICAL & CHEMICAL PROPERTIES

<b>PRODUCT WEIGHT</b>	13.84 lb/gal	1658 g/l
<b>SPECIFIC GRAVITY</b>	1.67	
<b>BOILING POINT</b>	212 - 213 °F	100 - 100 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	29%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	N.A.	
<b>pH</b>	8.0	

### **VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)**

0.13 lb/gal 16 g/l Less Water and Federally Exempt Solvents

0.10 lb/gal 11 g/l Emitted VOC.

Note: The above information is not intended for use in preparing product specifications.

## 10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 5 of 7  
Version: 1.1  
Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

### Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds.

## 11. TOXICOLOGICAL INFORMATION

### Component Toxicology Information

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

### Special Hazard Information on Components

<u>CAS Number</u>	<u>Component Name</u>	LC50 RAT	4HR	
471-34-1	Calcium Carbonate	LD50 RAT		Not Available
				Not Available

## 12. ECOLOGICAL CONSIDERATIONS

### Environmental Fate and Distribution

Complete information is not yet available.

### Environmental Effects

Complete information is not yet available.

### Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <=2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

## 13. DISPOSAL CONSIDERATIONS

# MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Page 6 of 7  
Version: 1.1  
Revision Date: March 4, 2011

## XTRABOND XB25 ACRYLIC LATEX SEALANT

### RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

Incinerate in approved facility. Do not incinerate closed container.

State or local laws may impose additional regulatory requirements regarding disposal.

## 14. TRANSPORT INFORMATION

### DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

### Ocean Shipment (IMDG)

Not subject to IMDG code.

### Air Shipment (IATA)

Not subject to IATA regulations.

## 15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

### EPA SARA Title III Chemical Listings

#### **Section 313 Toxic Chemicals (40 CFR 372.65C):**

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

### Supplemental State Compliance Information

#### **California**

Warning: This product contains chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

## 16. OTHER INFORMATION

Prepared by: Premier Industrial Supply, Inc.

# **MATERIAL SAFETY DATA SHEET**

**PREMIER INDUSTRIAL SUPPLY, INC.**

Page 7 of 7

Version: 1.1

Revision Date: March 4, 2011

## **XTRABOND XB25 ACRYLIC LATEX SEALANT**

The opinions expressed herein are those of qualified experts within Premier Industrial Supply Inc. These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. Since the use of the product is not within the control of Premier Industrial Supply Inc., each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

<http://www.xtrabond.com>